

# PA2806C-M 15W Ceiling light 4000K

## PRODUCT INFORMATION

|                     |                                   |
|---------------------|-----------------------------------|
| Product code        | IE60106                           |
| Product code (long) | IE-CL-CLR-15-1000-4000K-110       |
| Product description | PA2806C-M 15W Ceiling light 4000K |
| EAN code            | 5999097601069                     |
| Category            | Ceiling light                     |

## ELECTRICAL DATA

|                     |           |
|---------------------|-----------|
| Nominal wattage     | 15 W      |
| Rated wattage       | 15.0 W    |
| Nominal voltage     | 100-240 V |
| Operating frequency | 50-60 Hz  |
| Power factor        | > 0.9     |

## PHOTOMETRIC DATA

|   |               |
|---|---------------|
| Nominal luminous flux                   | 1000 lm       |
| Rated luminous flux                     | 1000 lm       |
| Nominal beam angle (half-peak value)    | 110°          |
| Rated beam angle (half-peak value)      | 110°          |
| Correlated colour temperature           | 4000 K        |
| Colour temperature designation          | neutral white |
| Colour rendering index (Ra)             | 80+ Ra        |
| Warm-up time to reach 60% of full light | <= 1.0 s      |

## MECHANICAL DATA

|                  |                  |
|------------------|------------------|
| Overall diameter | 226 mm           |
| Overall height   | 39 mm            |
| Mounting         | mounting bracket |

## LIFE SPAN

|                            |       |
|----------------------------|-------|
| Number of switching cycles | 15000 |
|----------------------------|-------|

## ADDITIONAL TECHNICAL INFORMATION

|                                       |                  |
|---------------------------------------|------------------|
| Starting time                         | < 0.5 s          |
| Optimum operating ambient temperature | -20 °C to +40 °C |
| Dimming                               | non-dimmable     |
| Electrical protection class           | Class II         |

