IE60087

15 W

> 0.9

1000 lm 1000 lm 110° 3000 K warm white 80+ Ra <= 1.0 s

15.0 W

100-240 V 50-60 Hz

5999097600871 Downlight

IE-DL-DL190x-15-1000-3000K-110 PA2907C 15W Downlight 3000K

PRODUCT INFORMATION

Ρ	roduct code
Ρ	roduct code (long)
Ρ	roduct description
E	AN code
C	Category

ELECTRICAL DATA

Nominal wattage	
Rated wattage	
Nominal voltage	
Operating frequency	
Power factor	

PHOTOMETRIC DATA

Nominal luminous flux	
Rated luminous flux	
Nominal beam angle (half-peak value)	
Rated beam angle (half-peak value)	
Correlated colour temperature	
Colour temperature designation	
Colour rendering index (Ra)	
Warm-up time to reach 60% of full light	

MECHANICAL DATA

Overall length	202 mm
Overall width	202 mm
Overall height	21 mm
Mounting	185 mm x 185 mm cuto

LIFE SPAN

Number of switching cycles

ADDITIONAL TECHNICAL INFORMATION

Starting time
Optimum operating ambient temperature
Dimming
Electrical protection class

< 0.5 s -20 °C to +40 °C non-dimmable Class II

15000





