PRODUCT INFORMATION

| Product code |
|---------------------|
| Product code (long) |
| Product description |
| EAN code |
| Category |

ELECTRICAL DATA

PHOTOMETRIC DATA

| Nominal luminous flux |
|---|
| Rated luminous flux |
| Nominal beam angle (half-peak value) |
| Rated beam angle (half-peak value) |
| Rated peak intensity |
| Correlated colour temperature |
| Colour temperature designation |
| Colour rendering index (Ra) |
| Warm-up time to reach 60% of full light |
| |

MECHANICAL DATA

| Overal diameter |
|-----------------|
| Overall height |
| Weight |
| Mounting |

LIFE SPAN

| Nominal life time |
|----------------------------|
| Rated life time |
| Number of switching cycles |

ADDITIONAL TECHNICAL INFORMATION

| Starting time |
|---------------------------------------|
| Optimum operating ambient temperature |
| Dimming |
| Electrical protection class |

IE60202 IE-DL-MQ603-24-2000-3000K-120 MQ603 24W 120° Downlight 3000K 59990976602028 Downlight

24 W 24.0 W 220-240 V 50-60 Hz > 0.9

2000 lm 2000 lm 120° 866 cd 3000 K warm white > 80 <= 1.0 s

> 240 mm 53 mm 720 g D200-210 mm cutout

35000 h 35000 h 15000

< 0.5 s -20 °C to +40 °C non-dimmable Class II





