PRODUCT INFORMATION

Product code
Product code (long)
Product description
EAN code
Category

ELECTRICAL DATA

Nominal wattage
Rated wattage
Nominal voltage
Operating frequency
Power factor
Power factor

PHOTOMETRIC DATA

Nominal luminous flux
Rated luminous flux
Nominal beam angle (half-peak value)
Rated beam angle (half-peak value)
Rated peak intensity
Correlated colour temperature
Colour temperature designation
Colour rendering index (Ra)
Warm-up time to reach 60% of full light

MECHANICAL DATA

Overal diameter	240 mm
Overall height	53 mm
Weight	720 g
Mounting	D200-210 mm cutout

LIFE SPAN

Nominal life time
Rated life time
Number of switching cycles

ADDITIONAL TECHNICAL INFORMATION

Starting time
Optimum operating ambient temperature
Dimming
Electrical protection class

< 0.5 s -20 °C to +40 °C non-dimmable Class II

35000 h 35000 h 15000







IE60204 IE-DL-MQ603-24-2000-5700K-120 MQ603 24W 120° Downlight 5700K 5999097602042 Downlight

24 W 24.0 W 220-240 V 50-60 Hz > 0.9

2000 lm 2000 lm 120° 866 cd 5700 K cool white > 80 <= 1.0 s