

E14 5W 160° LED Bulb 3000K G2

PRODUCT INFORMATION

| | |
|---------------------|-------------------------------|
| Product code | 60302 |
| Product code (long) | IE-E14-5-470-3000K-160-B-G2 |
| Product description | E14 5W 160° LED Bulb 3000K G2 |
| EAN code | 5999097603025 |
| Category | Retrofit |

ELECTRICAL DATA

| | |
|-------------------------------------|----------|
| Nominal wattage | 5W |
| Rated wattage | 5W |
| Nominal voltage | 220-240V |
| Operating frequency | 50/60Hz |
| Nominal current | 45 |
| Power factor | 0,5 |
| Wattage of equivalent filament lamp | 40W |

PHOTOMETRIC DATA

| | |
|---|------------|
| Nominal luminous flux | 470 lm |
| Rated luminous flux | 470 lm |
| Rated useful luminous flux | 94 |
| Nominal beam angle (half-peak value) | 160° |
| Rated beam angle (half-peak value) | 160° |
| Correlated colour temperature | 3000K |
| Colour temperature designation | warm white |
| Colour rendering index (Ra) | 80 |
| Colour consistency | < 6 |
| Warm-up time to reach 60% of full light | < 0.5 s |
| Suitable for accent lighting | N |

MECHANICAL DATA

| | |
|------------------|-------|
| Overall diameter | 45 mm |
| Overall height | 78 mm |
| Lamp shape | Globe |

LIFE SPAN

| | |
|---|------------|
| Nominal life time | 15 000 hrs |
| Rated life time | 15 000 hrs |
| Number of switching cycles | 7500 |
| Lumen main.fact.at end of nom.life time | >70% |

ADDITIONAL TECHNICAL INFORMATION

| | |
|---------------------------------------|---------------|
| Starting time | <0,2S |
| Optimum operating ambient temperature | -20°C - +40°C |
| Lamp cap | E14 |
| Lamp finish | frosted |
| Dimming | Non-dimmable |
| Energy efficiency class | A+ |
| Energy consumption | 5 kWh/100h |
| IP rating | IP20 |

