PRODUCT INFORMATION

Product code
Product code (long)
Product description
EAN code
Category

ELECTRICAL DATA

Nominal wattage
Rated wattage
Nominal voltage
Operating frequency
Nominal current
Power factor
Wattage of equivalent filament lamp

PHOTOMETRIC DATA

Nominal luminous flux	470 lm
Rated luminous flux	470 lm
Rated useful luminous flux	94
Nominal beam angle (half-peak value)	160°
Rated beam angle (half-peak value)	160°
Correlated colour temperature	3000K
Colour temperature designation	warm white
Colour rendering index (Ra)	80
Colour consistency	< 6
Warm-up time to reach 60% of full light	< 0.5 s
Suitable for accent lighting	Ν

MECHANICAL DATA

Overal diameter	37 mm
Overall height	106 mm
Lamp shape	Candle

LIFE SPAN

Nominal life time	15 000 hrs
Rated life time	15 000 hrs
Number of switching cycles	7500
Lumen main.fact.at end of nom.life time	>70%

ADDITIONAL TECHNICAL INFORMATION

Starting time	<0.2S
Optimum operating ambient temperature	-20°C - +40°C
Lamp cap	E14
Lamp finish	frosted
Dimming	Non-dimmable
Energy efficiency class	A+
Energy consumption	5 kWh/100h
IP rating	IP20

60299 IE-E14-5-470-3000K-160-C-G2 E14 5W 160° LED Candle 3000K G2 5999097602998 Retrofit

5W 5W 220-240V 50/60Hz 45 0,5 40W





