

HHB 15W Floodlight 5700K

PRODUCT INFORMATION

Product code	IE60171
Product code (long)	IE-FL-HHB-15-1250-5700K-120
Product description	HHB 15W Floodlight 5700K
Category	Floodlight

ELECTRICAL DATA

Nominal wattage	15 W
Rated wattage	15.0 W
Nominal voltage	220-240 V
Operating frequency	50-60 Hz

PHOTOMETRIC DATA

Nominal luminous flux	1250 lm
Rated luminous flux	1250 lm
Nominal beam angle (half-peak value)	120°
Rated beam angle (half-peak value)	120°
Correlated colour temperature	5700 K
Colour temperature designation	cool white
Colour rendering index (Ra)	70+ Ra
Colour consistency	<= 6 SDCM
Warm-up time to reach 60% of full light	<= 1.0 s

MECHANICAL DATA

Overall length	176 mm
Overall width	75 mm
Overall height	58.5 mm
Tilting	Rotatable base

LIFE SPAN

Nominal life time	15000 h
Rated life time	15000 h
Number of switching cycles	15000
Lumen main.fact.at end of nom.life time	70%

ADDITIONAL TECHNICAL INFORMATION

Starting time	< 0.5 s
Optimum operating ambient temperature	-25 °C to +35 °C
Lamp cap	E27
Lamp finish	Clear
Dimming	non-dimmable
Energy efficiency class	A+
Energy consumption	15 kWh/1000h

