## PRODUCT INFORMATION

Product code
Product code (long)
Product description
EAN code
Category

## ELECTRICAL DATA

Nominal wattage
Rated wattage
Nominal voltage
Operating frequency
Nominal current
Power factor
Wattage of equivalent filament lamp

#### PHOTOMETRIC DATA

Nominal luminous flux	495 lm
Rated luminous flux	550 lm
Rated useful luminous flux	79
Nominal beam angle (half-peak value)	105°
Rated beam angle (half-peak value)	105°
Correlated colour temperature	3000K
Colour temperature designation	warm white
Colour rendering index (Ra)	80
Colour consistency	< 6
Warm-up time to reach 60% of full light	< 0.5 s
Suitable for accent lighting	Ν

# MECHANICAL DATA

Overal diameter	50 mm
Overall height	56,5 mm
Lamp shape	GU10
Weight	0,04 kg

### LIFE SPAN

Nominal life time	15 000 hrs
Rated life time	15 000 hrs
Number of switching cycles	12500
Lumen main.fact.at end of nom.life time	>70%

### ADDITIONAL TECHNICAL INFORMATION

Starting time	<0.55
Optimum operating ambient temperature	-10°C - +50°C
Lamp cap	GU10
Lamp finish	Milky cover
Dimming	Non-dimmable
Energy efficiency class	A+
Energy consumption	7 kWh/100h
IP rating	IP42

60309 IE-GU10-7-550-3000K-105-G2 GU10 7W 105° LED Spot 3000K G2 5999097603094 Retrofit

7W 7W 220-240V 50/60Hz 70 0,5 45W

1	INE'SA	
	0 6	



