

GC617 150W 60° Highbay 5700K

PRODUCT INFORMATION

Product code	IE60232
Product code (long)	IE-HB-GC617-150-15000-5700K-60
Product description	GC617 150W 60° Highbay 5700K
Category	High-bay

ELECTRICAL DATA

Nominal wattage	150 W
Rated wattage	150.0 W
Nominal voltage	220-240 V
Operating frequency	50-60 Hz
Power factor	0.95

PHOTOMETRIC DATA

Nominal luminous flux	15000 lm
Rated luminous flux	15000 lm
Nominal beam angle (half-peak value)	60°
Rated beam angle (half-peak value)	60°
Rated peak intensity	18700 cd
Correlated colour temperature	5700 K
Colour temperature designation	cool white
Colour rendering index (Ra)	70+ Ra
Colour consistency	<= 6 SDCM
Warm-up time to reach 60% of full light	<= 1.0 s

MECHANICAL DATA

Overall length	671 mm
Overall width	271 mm
Overall height	218 mm
Mounting	hook

LIFE SPAN

Nominal life time	50000 h
Rated life time	50000 h
Number of switching cycles	15000
Lumen main.fact.at end of nom.life time	70%

ADDITIONAL TECHNICAL INFORMATION

Starting time	< 0.5 s
Optimum operating ambient temperature	-30 °C to +45 °C
Lamp finish	powder coated die-ca
Dimming	non-dimmable
Electrical protection class	Class I
IP rating	IP65

