


SPECIFICATION FOR APPROVAL

Package Dimensions




Material's Picture



Notes

1. All dimensions are in millimeters (inches).
2. Tolerance is $\pm 0.25\text{mm}$ (0.010") unless otherwise noted.
3. Protruded resin under flange is 1.0mm (0.04") max.
4. Lead spacing is measured where the leads emerge from the package.
5. Specifications are subject to change without notice.

Spatial Distribution



PART NUMBER	REV	PAGE	DATE
P100WW6530B403200	R101	1/4	2009-11-27

SPECIFICATION FOR APPROVAL

Electrical / Optical Characteristics at TA=25°C


Parameter	Symbol	Min.	Typ.	Max.	Unit	Test Condition
Luminous Intensity	Φ	3200	3400	3600	lm	IF =1400mA
Viewing Angle	2 θ 1/2		140		deg	IF =1400mA
Domain Wavelength	Tc	6000	6500	7000	K	IF =1400mA
Spectral Line Half-Width	$\Delta \lambda$				nm	IF =1400mA
Forward Voltage	VF	32,00	34,00	36,00	V	IF =1400mA
Reverse Current	IR			20	μ A	VR = 5V

Absolute Maximum Ratings at TA=25°C

Parameter	Maximum Rating
Power Dissipation	40W
Peak Forward Current (1/10 Duty Cycle, 0.1ms Pulse Width)	5000mA
Continuous Forward Current	1400mA
Derating Linear From 30°C	0.8mA/°C
Reverse Voltage	5V
Operating Temperature Range	-35°C to + 60°C
Storage Temperature Range	-35°C to + 60°C
Lead Soldering Temperature [1.6mm(.063") From Body]	300°C for 5 Seconds

PART NUMBER	REV	PAGE	DATE
P100WW6530B403200	R101	2/4	2009-10-30



SPECIFICATION FOR APPROVAL**Chromaticity Coordinate Groups**








PART NUMBER	REV	PAGE	DATE
P100WW6530B403200	R101	3/4	2009-10-30

SPECIFICATION FOR APPROVAL

HIGH POWER LED Typical Electro-Optical Characteristics Curves





- ① Blue Lamp<InGaN>
- ② White Lamp<InGaN>
- ③ Pure Green Lamp<InGaN>
- ④ Yellow Green Lamp<AlInGaP>
- ⑤ Red Lamp<AlInGaP>
- ⑥ Infrared Lamp<850nm>

PART NUMBER	REV	PAGE	DATE
P100WW6530B403200	R101	4/4	2009-10-30